


Begin to enjoy your home living EXPERIENCE with the

# Opus II

patio door



ROYAL  
*Opus II*  
all vinyl  
patio door

 ROYAL Building Products

[www.royalplast.ca](http://www.royalplast.ca) | Woodbridge, Ontario 1.888.339.9085  
Terrebonne, Quebec 1.866.777.1210

Royal Building Products is not responsible for any errors or omissions,  
and reserves the right to modify the design and product specifications without prior notice.



BOPUS2E1 2U1

ROYAL  
*Opus II*  
all vinyl  
patio door

The style and comfort  
of your home start with *Opus II*



 ROYAL Building Products

# Standard PREMIUM Features



## Frame

- 5 5/8" all PVC multi-chambered profile frame system
- With or Without integrated Nail Fin application
- Mechanically fastened frame system
- Full length dual weather stripping in all jambs and sash components
- Full length bulb seal in operable jamb side for increased air-tightness
- High Performance 10 degree slope for superior water resistance and drainage
- All exposed aluminum is anodized to prevent corrosion
- Standard jamb pocket cover on the interior fixed side for a smooth and clean finish
- Exterior & Interior mulling grooves for brickmold, transom and sidelight attachments

## Sash

- Fully welded vinyl sashes available in 1" or 1 1/4" or 1 3/8" Insulated Glass System with many high energy-efficient glass options for the most extreme cold weather regions
- All stiles, interlocks, and horizontal rails are metal re-inforced for extreme wind load resistance
- Unique internal drainage system to minimize risk of seal failures
- Standard single point mortise lock and optional twin-point locking system is available
- Standard 1" IG unit system available in many high energy-efficient glass options
- Available 1 3/8" or 1 1/4" TRUE Triple IG Glass system with various glass options including LoE and internal grids
- Adjustable nylon (made of acetyl rod) tandem panel rollers, classified as ABEC-5 Precision Ball Bearing system, providing years of continuous smooth gliding operation



## Screen

- Exclusive nylon screen roller system is designed with a unique spring-loaded suspension and side adjustment screw for ease of installation. Each wheel is precision-machined using a highly tensile strength nylon material made of acetyl rod
- Heavy-duty extruded aluminum screen frame with fibreglass mesh for easy removal and adjustability



## OPTIONS

- Extensive choice of glass, grid, and hardware options available

## COLOURS

- Solid PVC: Cream White #137 / Blue White #141 / Tan #349
- Painted colours available using the Royal Bond™ Spectraccoat™ Technology  
*RoyalPlast Colour swatch available upon request.*



## PERFORMANCE DATA

The **Opus II** patio door meets and exceeds the following testing standards for North America: AAMA/WDMA/CSA 101/1.S.2/A440-08 and CAN/CGSB/82.1-M89  
Size Tested: 71" x 81 1/8" OX/XO

	Air Tightness	Water Resistance	Wind-load Resistance	Forced Entry (Grade 10)	Ease of Operation	Energy Star
CAN/CGSB/82.1-M89	A3	B4	C3	F1	E3	Energy Star Qualified
AAMA/WDMA/CSA 101/1.S.2/A440-08	Class R-PG45-SD (with A3 for Canadian Air/level)					

STANDARD SIZES	WIDTH								HEIGHT
	5 ft.	6 ft.	8 ft.	7.5 ft.	9 ft.	12 ft.	10 ft.	12 ft.	
Nominal Dimensions X = Operating Sash O = Fixed Sash	$\begin{matrix} X & O \\ O & X \end{matrix}$	$\begin{matrix} X & O \\ O & X \end{matrix}$	$\begin{matrix} X & O \\ O & X \end{matrix}$	$\begin{matrix} O & X & O \end{matrix}$	$\begin{matrix} O & X & O \end{matrix}$	$\begin{matrix} O & X & O \end{matrix}$	$\begin{matrix} O & X & X & O \end{matrix}$	$\begin{matrix} O & X & X & O \end{matrix}$	6'8" or 6'10"
Exterior Frame Dimensions	59"	71"	95"	88 1/16"	106 1/16"	142 1/16"	115 3/4"	139 3/4"	79 1/2"
Minimum Rough Opening	59 3/4"	71 3/4"	95 3/4"	88 13/16"	106 13/16"	142 13/16"	116 1/2"	140 1/2"	80"

OR

Exterior Frame Dimensions	58 5/8"	70 5/8"	94 5/8"	87 1/2"	105 1/2"	141 1/2"	115"	139"	81 1/8"
Minimum Rough Opening	59 3/8"	71 3/8"	95 3/8"	88 1/4"	106 1/4"	142 1/4"	115 3/4"	139 3/4"	81 5/8"

## WARRANTY

The Royal **Opus II** all vinyl patio door is manufactured and delivered with a Limited 20 Year Warranty: 20 years on PVC - 20 years against glass seal failure - 1 year on hardware components  
Please refer to our warranty document for complete details on limitations and exclusions